
SIGMA WATERWORKS

RMB1015NSW
MEDIUM DUTY POLYMER ENCLOSURE

RMB1015NSW MEDIUM DUTY
NON-STACKING STRAIGHT WALL METER BOX

Meter Box

- SIGMA Waterworks Non-Stacking Straight Wall Meter Boxes are produced using Polyethylene regrind and virgin resins.
- Wall thickness shall be 1/2" constructed with three layers. The center of which is foam insulation, and such that when buried, it will support an incidental traffic load with the appropriate traffic rated lid.
- The box will have two pre-formed pipe entry areas, located at the center of each end (short side) of the box.
- Interior shall be smooth and optional bright white polyethylene.
- Straight Wall Meter Box shall have an integral flat settling plate around the base.





Part Number	"D" Dim. (In.)
RMB101512NSW	12

LOAD RATING DEPENDS ON BOX/LID COMBINATION

See page 2 for lid options & ratings.

Dimensions





Made in the USA

SIGMA Waterworks
700 Goldman Drive
Cream Ridge, NJ 08514

Phone: 800.999.2550

SIGMA WATERWORKS


RMB1015NSW


MEDIUM DUTY POLYMER ENCLOSURE


LID OPTIONS

FOR RMB1015NSW METER BOX

LOAD RATING DEPENDS ON BOX/LID COMBINATION







FEATURE	SPE LYTE LID	SPE TUFF LID	SPE MAXX-DI LID
VLR‡	Pedestrian	H20-A16	H20-A16
Material	100% Virgin Polymer†	100% Virgin Polymer†	65-45-12 Ductile Iron per ASTM A536
Density	0.935 to 0.941 g/cc	0.935 to 0.941 g/cc	—
Manufacturing	Roto-Molding	Injection Molding	—
ADA Slip Resistant*	✓	✓	✓
Negligible Signal dB Loss**	✓	✓	—
Additional Markings***	✓	✓	—
Colors	Black, Gray, Purple, Green, Blue	Black, Gray, Purple, Green, Blue	Bare, Black, Gray, Purple, Green, Blue
Detectable	✓	✓	✓
No-Float	Locking Features Available Upon Request	✓	✓
Read Options	Plain, Flip-Read, Touch-Read	Plain, Touch-Read	Plain, Flip-Read, Touch-Read

Notes

‡ Higher VLR available upon request.
† For consistency in material & quality; UV inhibitors to be added, supports RF-transparency.
* Meets ADA slip resistant requirements: coefficient of static friction @ 0.73 (dry) and not less than 0.50 (wet).
** Signal strength dB loss is negligible when compared to a box with no lid.
*** Additional markings such as “SEWER”, “WATER”, blank, or township specific are available.
— Not listed for this lid.

Made in the USA

SIGMA Waterworks
700 Goldman Drive
Cream Ridge, NJ 08514

Phone: 800.999.2550